

SAFETY DATA SHEET**1. IDENTIFICATION OF MATERIAL & COMPANY DETAILS****Product Name:** 720 ISOCYANATE FREE 2 PACK (PART 'A')**Product description:** 2K Iso-free Part A Base
Recommended Use: Use according to manufactures Technical Data Sheet
CAS Number: Not Applicable**Company Name:** Lacnam Paints Australia
Address: 76-80 Mandoon Road, Girraween, NSW 2145
Email: sales@lacnam.com.au
Telephone Number: (02) 9688-1999**Emergency Number:** 0419 260 572 (after hours)**2. HAZARDS IDENTIFICATION****HAZARDOUS SUBSTANCE-DANGEROUS GOODS:**Classified as hazardous according to criteria of Work Safe Australia
Classified as dangerous according to Dangerous Good Code**Signal Word:** DANGER**GHS Classification:**Aspiration Hazard: Category 1
Acute Aquatic Toxicity: Category 3
Chronic Aquatic Hazard: Category 2
Acute Toxicity Inhalation: Category 4
Acute Toxicity Dermal: Category 4
Eye Irritation Corrosion/Hazard: Category 2B
Flammable Liquid: Category 2
Skin Corrosion/Irritation: Category 2
STOT-SE: Category 3 (narcotic)
STOT-RE: Category 2
Toxic to Reproduction: Category 1A**Hazard Statements:**H226 - Flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H336 - May cause drowsiness and dizziness
H360 - May damage fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated use
H402 - Harmful to aquatic life**Non-GHS Hazard Statement:**

AUH066 – Repeated exposure may cause skin dryness and cracking

SAFETY DATA SHEET

Name: 720 Iso-Free Part A
Page 2 of 12
Date of Issue: 01/08/2025

2. HAZARDS IDENTIFICATION

General Precautionary Statements:

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P103 - Read label before use

Prevention Precautionary Statements:

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233+234 - Keep container tightly closed. Keep only in original container
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/light/.../equipment
P242+243 - Use only non-sparking tools. Take precautionary measures against static discharge
P260 - Do not breathe dust/fume/gas/mist/vapours/spray
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray
P262 - Do not get in eyes, on skin, or on clothing
P264 - Wash all exposed skin area thoroughly after handling
P270 - Do not eat, drink, or smoke when using this product
P272 - Contaminated work clothing should not be allowed out of the workplace
P273 - Avoid release to the environment
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P285 - In case of inadequate ventilation wear respiratory protection

Response Precautionary Statements:

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P302+352 - IF ON SKIN: Wash with soap and water
P303+361+353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P306+360 - IF ON CLOTHING: Rinse immediately contaminated clothing and skin with plenty of water before removing clothes
P308+313 - IF exposed or concerned: Get medical advice/attention
P314 - Get Medical advice/attention if you feel unwell
P321 - Specific treatment: Immediate First Aid Measures Refer Section 4 of Safety Data Sheet
P333+313 - If skin irritation or a rash occurs: Get medical advice/attention
P337+313 - If eye irritation persists get medical advice/attention
P363 - Wash contaminated clothing before reuse
P370+P378 - In case of fire: Use Foam, Dry Chemical Powder, Carbon Dioxide, Fine Water Spray or Fog (for large fires only) for extinction
P391 - Collect spillage

Storage Precautionary Statements:

P403+233+235: Store in a well-ventilated place. Keep container tightly closed. Keep cool

Disposal precautionary statements:

P501: Dispose of contents/container to authorised landfill. Refer to State/Local land Management Authority.

SAFETY DATA SHEET

Name: 720 Iso-Free Part A
Page 3 of 12
Date of Issue: 01/08/2025

3. COMPOSITION/INFORMATION OF INGREDIENTS

Component Name:	CAS Number:	Proportion % Weight:
Epoxy Functional Acrylic Resin	Proprietary	40-70%
Pigments	Proprietary	10-45%
Xylene	1330-20-7	5-10%
Propylene glycol methyl ether acetate	108-65-6	1-5%
Butyl Acetate	123-86-4	1-5%
Additives	Proprietary	1-5%
Ethyl 3-Ethoxypropionate	763-69-9	0-5%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or
Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation:

- If inhalation of mists, fumes or vapour causes irritation to the nose, throat or lungs, causing coughing, wheezing or impaired motor skills, remove patient to fresh air.
- If symptoms persist, obtain medical advice.

Skin:

- Remove all contaminated clothing and footwear.
- Wash contaminated area thoroughly with soap and water as soon as reasonably practicable.
- Seek medical attention if irritation occurs.

Eyes:

- Immediately flush eyes with large amounts of water for at least 15 minutes.
- Method of irrigation; keep eyelids apart and away from eyes, routinely lift upper and lower eyelid away from eye while flushing with water.
- Removal of contact lenses should only be performed by skilled personnel.
- Transport to the nearest medical facility for additional treatment.

Swallowed:

- Do not induce vomiting, place person's face downwards, head lower than hips to prevent vomit entering lungs.
- Rinse mouth with water. Give water to drink.
- Avoid giving patient milk or oils.
- Observe patient carefully; withhold water if patient display signs of drowsiness or reduced awareness and possible unconsciousness.
- Seek medical advice.

First Aid Facilities:

- Ensure that eye wash bath and safety showers are readily accessible.

Advice to Doctor:

- Treat the patient symptomatically.

For acute or short-term repeated exposure to petroleum distillates or related hydrocarbons the primary threat to life is respiratory failure from ingestion and/or inhalation. Patients should be quickly evaluated for signs of respiratory distress (e.g., cyanosis, tachypnoea, intercostal retraction, or obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ 50 mm Hg) should be intubated.

SAFETY DATA SHEET

Name: 720 Iso-Free Part A
Page 4 of 12
Date of Issue: 01/08/2025

5. FIRE FIGHTING MEASURES

Hazchem Code: 3YE

Fire & Explosion Hazard:

- Liquid and vapours are flammable.
- Moderate explosion hazard when exposed to heat or flame.
- Vapour may travel a considerable distance to source of ignition.
- Containers may rupture violently when exposed to extreme heat.
- On combustion the following products may be produced, Carbon Dioxide, Carbon Monoxide, Soot and Toxic smoke.
- Avoid contamination with oxidising agents i.e., nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Fire Fighting:

- Evacuate immediate area of non-emergency personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Wear full protective equipment including self-contained breathing apparatus.
- Fight fire from a safe distance, with adequate cover and safe fire escape exit.
- Use foam, dry chemical, or carbon dioxide extinguishers. Fine water spray may be used to cool containers to prevent vapour pressure build up.
- Prevent water runoff from entering storm water drains or waterways.

6. ACCIDENTAL RELEASE MEASURES

Minor Spills:

- Clean up all spills immediately.
- Eliminate all sources of ignition
- Wear full protective clothing (refer section 8)
- Avoid breathing vapours and contact with skin and eyes.
- Contain and absorb using earth, sand, vermiculite, or other absorbent material. DO NOT USE sawdust, this is flammable.
- Collect residues in a flammable waste container and dispose of according to local waste management regulations.
- Do not allow product to enter storm water drains or waterways.
- Immediately remove all contaminated clothing after containment.

Major Spills:

- Evacuate personnel from immediate area and move upwind.
- Alert Fire Brigade of location and nature of hazard
- Eliminate all sources of ignition
- Wear full protective clothing (refer section 8)
- If safe to do so eliminate source of spillage.
- Avoid breathing vapours and contact with skin and eyes.
- Prevent, by any means available, spillage from entering storm water drains or water ways.
- If possible, contain and absorb using earth, sand, vermiculite, or other absorbent material. DO NOT USE sawdust, this is flammable.
- Use only anti-spark/ anti-static equipment to contain and remove spillage.
- Recoverable product should be collected into labeled flammable containers for recycling.
- Collect residues in a flammable waste container and dispose of according to local waste management regulations.
- Immediately remove all contaminated clothing after containment.

SAFETY DATA SHEET

Name: 720 Iso-Free Part A
Page 5 of 12
Date of Issue: 01/08/2025

7. HANDLING AND STORAGE

Safe Storage:

- Store product in accordance with Local State, or Territory Dangerous Goods Regulations.
- Keep containers closed when not in use.
- Store away from sources of heat or ignition in a cool dry well-ventilated area.
- Do store in areas where vapours may be concentrated i.e., pits, basements, or unventilated storage area.
- Do not store or load on the same vehicle as Class 1, Class 2.1, Class 2.3, Class 4.2, Class 5.1, Class 5.2 or Class 7 materials.

Precautions for safe handling:

- Do not smoke in storage/work area.
- Avoid skin and eye contact and breathing in vapour.
- All material handling equipment in work area must be flameproof.
- All nearby equipment should be earthed
- All potential sources of ignition must be eliminated from storage/work area.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Occupational Exposure Limits: No value assigned for this specific product by Safe Work Australia: Hazardous Substances Information System (HSIS).

Concentration Cut-off Levels:

A concentration cut-off level for a substance is the level (expressed as a percentage on a weight/weight basis for solids and liquids and a volume/volume basis for gases) at and above which that substance is classified as a hazardous substance. A mixture is classified as a hazardous substance if it contains at least one ingredient at a concentration equal to, or above, the lowest concentration cut-off level given for that ingredient. Concentration cut-off levels refer to health hazards only and are not associated with the physicochemical or environmental hazards of a substance. The health effects of certain types of hazardous substances are regarded as additive. Due to additive effects, a mixture may be classified as hazardous even if all the individual substances in the mixture are present at levels below their respective cut offs.

Chemical Name	CAS. No	TWA (8hr)		STEL		Source	Notices	%Weight
		ppm	mg/m3	ppm	mg/m3			
Titanium Dioxide	13463-67-7		10(a)			NZWES	Inhalation	<30.00%
Xylene	1330-20-7	80	350	150	655	Eu;A		<15.00%
Propylene glycol methyl ether acetate	108-65-6	50	274	100	548			<05.00%
Butyl Acetate	123-86-4	150	713	200	950			<05.00%
Carbon Black	1333-86-4		3			A		<05.00%
Barium Sulphate	7727-43-7		10(a)			NZWES	Inhalation	<03.00%
Naphtha (petroleum), hydrosulfurized heavy	64742-82-1		Not Defined					<00.20%
Low BP Naphtha Unspecified	8052-41-3		790					<.00.20%

Source:

- A Listed in the National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC: 1003(1995).
- Eu Listed in the European Union's Annex I of the EEC Council Directive 67/548/EEC (as updated by EEC Council Directive 2001/59/EC).
- NIOSH National Institute for Occupational Safety and Health.
- NZWES New Zealand Workplace Exposure Standards and Biological Exposure Indices 7th edition
- Sk Absorption through the skin may be a significant source of exposure.
- (a) The value for inhalable dust containing no asbestos and less than 1.0% free silica.

SAFETY DATA SHEET

Name: 720 Iso-Free Part A
Page 6 of 12
Date of Issue: 01/08/2025

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Based on available information on hazardous components of this product, the recommended exposure limit, (TWA) is 100 ppm.

Exposed individuals may be desensitised to product and are not reasonably expected to be warned, by smell, that exposure standard is being exceeded.

If the TWA concentration of ANY of the components is exceeded the individual is deemed to be over exposed.

Engineering Controls: Use process enclosures, local exhaust ventilation or other engineering controls to maintain worker exposure to airborne contaminants below any recommended or statutory limits. Keep containers closed when not in use. Ensure exhaust air does not contaminate other workspaces.

Vapour heavier than air - Prevent vapours concentrating in work pits, tanks or sumps. DO NOT enter confined spaces where vapour may have collected.

Ensure electrical equipment is in accordance with applicable regulations.

Equipment used to transfer product should be adequately earthed.

Ventilation equipment should be explosion/flame resistant.

Do not use near ignition sources.

Personal Protection: Avoid contact with skin and eyes. Wear suitable clothing such as impervious overalls, PVC, or Neoprene gloves, and safety goggles. Where workplace ventilation is assessed as inadequate and vapours/mists are generated, the use of an approved Half or Full-Face Respirator with Type A-P Filter complying with Australian Standards AS1715/1716 is recommended. Select a filter suitable for organic gases and vapours rated for; [boiling point > 65°C]. If working in confined spaces with inadequate ventilation, wear an air-fed full-face mask.



**Confined Space
Application:**



Flammability: Highly flammable. Avoid heat and sources of ignition. Container should be earthed when pouring.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance: Coloured viscous liquid.

Boiling/Melting Point (°C): 125/ Not available

Vapour Pressure: Not available

Specific Gravity: 0.95 - 1.15

Flashpoint (°C): >23

Auto-ignition temperature (°C): 370

Flammability Limits (% by Volume): 1-12

Solubility in Water: Not available

10. STABILITY AND REACTIVITY:

Chemical stability: Stable under normal conditions of use.

Do not store: In areas of extreme heat generated by naked flame or heating element.
In the presence of incompatible materials. Refer Section 7.

Incompatible materials: Do not store with Reactive or oxidizing agents.

Hazardous combustion: Carbon Dioxide, Carbon Monoxide, Soot and Toxic smoke.

Hazardous reactions: Under normal ambient conditions hazardous polymerization will not occur.

SAFETY DATA SHEET

Name: 720 Iso-Free Part A
Page 7 of 12
Date of Issue: 01/08/2025

11. TOXICOLOGICAL INFORMATION:

No value has been assigned for 720 Iso-Free Part A. Depending on colour, toxicity limits are recorded for individual components that may be present.

Acute - Swallowed: May cause irritation to mouth, throat, and digestive tract. Large dose may cause drowsiness and may lead to unconsciousness.

Acute - Eye: Irritating to the eyes.

Acute - Skin: Irritating to the skin. Has a degreasing action on the skin. Repeated or prolonged skin contact may lead to contact dermatitis and toxic effects.

Acute - Inhaled: Vapour may be an irritant to mucous membranes and respiratory tract.

Inhalation of vapour can result in headaches, dizziness, and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and, if exposure is prolonged, unconsciousness. Harmful if inhaled.

Chronic: Repeated or prolonged exposure to this chemical could result in central nervous system disorders.

Acute Toxicity: Refer Table 1 Section 16:

Chemical Name	Cas.No	Result	Species	Dose	Exposure
Titanium dioxide (dust)	13463-67-7	LD50 Oral LD50 Oral LD50 Dermal LC50 Inhalation	Rat Mouse Rabbit Rat	>10000mg/kg >10000mg/kg >10000mg/kg >6.8mg/l	4 hours
Synthetic amorphous Silica (dust)	112929-00-8	LD50 Oral	Human	>15000mg/kg	
Carbon Black (dust)	1333-86-4	LD50 Oral	Rat	>8000mg/kg	
Bismuth Vanadate (dust)	14059-33-7	LD50 Oral LC50 Inhalation	Rat Rat	>5000mg/kg >5.1 mg/l	4 Hours
Phthalocyanine Blue (dust)	147-14-8	LD50 Oral LD50 Dermal	Rat Rat	>5000mg/kg >1000mg/kg	
Monoazo Red (dust)	2786-76-7	LD50 Oral	Rat	>2000mg/kg	
Isoindolinone Yellow (dust)	36888-99-0	LD50 Oral	Rat	>10000mg/kg	
Ferric Oxide (dust)	1310-14-1	LD50 Oral	Rat	>5000mg/kg	
Red Oxide (dust)	1309-37-1	LD50 Oral	Rat	>5000mg/kg	
Phthalocyanine Green (dust)	1328-53-6	LD50 Oral	Rat	>15000mg/kg	
Aluminium Powder	7429-90-5	LD50 Oral LC50 Inhalation	Rat Rat	>2000mg/kg >888mg/kg	4 Hours
Bentonite Clay (dust)	68953-58-2	LC50 Oral LC50 Inhalation	Rat Rat	>5000mg/kg >200mg/kg	
Butyl Acetate	123-86-4	LD50 Oral	Rat	14,130mg/kg	
Ethyl 3-Ethoxypropionate	763-69-9	LD50 Oral LD50 Oral LD50 Dermal	Rat (male) Rat (female) Rabbit (male)	>5000mg/kg >4300mg/kg 4080mg/kg	
Propylene glycol methyl ether acetate	108-65-6	LD50 Oral LD50 Dermal	Rat Rabbit	>5000mg/kg >5000mg/kg	
Xylene	1330-20-7	LD50 Oral LD50 Dermal LC50 Inhalation	Rat Rabbit Rat	>2000mg/kg >2000mg/kg >20mg/l	4 hours
Ethyl benzene	100-41-4	LD50 Oral LD50 Dermal LC50 Inhalation	Rat Rabbit Rat	>3500mg/kg >5000mg/kg >55000mg/L	2 hours
Dipropylene glycol monomethyl ether	34590-94-8	LD50 Oral	Rat	>5152mg/kg	
2-methylpropan-1-ol	78-83-1	LD50 Oral LD50 Dermal LC50 Inhalation	Rat Rabbit Rat	3350mg/kg 3460mg/kg 5.25mg/l	5 hours
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	LD50 Oral LD50 Dermal LC50 Inhalation expected to be low toxicity	Rat Rat Rat	>2000mg/kg >2000mg/kg Greater than near saturated vapour concentration	4 hours

SAFETY DATA SHEET

Name: 720 Iso-Free Part A
Page 8 of 12
Date of Issue: 01/08/2025

12. ECOLOGICAL INFORMATION:

No value has been assigned for 720 Iso-Free Part A. Depending on colour, Aquatic Ecotoxicity Results are recorded for individual components that may be present.

- Prevent release into the environment.
- Do not discharge into sewer or waterways.
- May cause adverse effects to marine organisms.
- May cause adverse effects to marine environment

This product if spilled into waterways is expected to have similar characteristic to oil, creating a surface film, emulsion, or sludge at or beneath the water surface depending on prevailing conditions.

Aquatic Ecotoxicity

Chemical Name	Cas.No	Species	Result	Method	Exposure
Carbon Black (dust)	1333-86-4	Fish (Brachydanio rerio) Water Flea (Daphnia Magna) Algae (Scenedesmus subspicatus)	LC50 >1000mg/L EC50>5600mg/L EC50>10000mg/L	OECD 203 OECD 202	96 hours 24 hours 72 hours
Ferric Oxide (dust)	1310-14-1	Fish (golden orfe, leuciscus idus)	LC50>1000mg/L		
Bismuth Vanadate (dust)	14059-33-7	Fish (Brachydanio rerio) Water Flea (Daphnia Magna) Algae Microorganisms	LC50 - 10-100mg/l EC50 - 10-100mg/l EC50 - 10-100100mg/l EC50 - >10000mg/l	OECD 202 OECD 201	96 hours 48 hours 72 hours 16 hours
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	Fish Aquatic Invertebrates Algae Microorganisms	Toxic: LL/EL/IL50 1-10mg/l Toxic: LL/EL/IL50 1-10mg/l Toxic: LL/EL/IL50 1-10mg/l Practically nontoxic LL/EL/IL50 >100mg/L		
Xylene	1330-20-7	Fish Aquatic Invertebrates Algae Microorganisms	Toxic: LL/EL/IL50 1-10mg/l Toxic: LL/EL/IL50 1-10mg/l Toxic: LL/EL/IL50 1-10mg/l Practically nontoxic LL/EL/IL50 >100mg/l		
Ethyl Benzene	100-41-4	Fish (fathead minnow) Fish (sheepshead minnow) Fish (guppy)	LC50 - 423-48.5mg/l LC50 - 275mg/l LC50 - 97.1mg/l		96 hours 96 hours 96 hours
Butyl Acetate	123-86-4	Fish (fathead minnow) Water Flea (Daphnia Magna) Algae	LC50 - 18mg/l LC50 - 44mg/l EC50 - 648/mg/l		96 hours 48 hours 72 hours
Ethyl 3-Ethoxypropionate	763-69-9	Fish (fathead minnow) Water Flea (Daphnia Magna) Algae (Pseudokirchneriella subcapitata) Microorganisms (Bacteria)	LC50 - 88mg/l LC50 - >95mg/l EC50 - >114.86mg/l IC50 - >5000mg/l		96 hours 48 hours 72 hours 16 hours
Propylene glycol methyl ether acetate	108-65-6	Fish (Oncorhynchus mykiss) Water Flea (Daphnia Magna) Algae (Pseudokirchneriella subcapitata)	LC50 - 134mg/l EC50 - 408mg/l ErC50 - >1000mg/l		96 hours 48 hours 96 hours
2-methylpropan-1-ol	78-83-1	Fish (fathead minnow) Water Flea (Daphnia Magna)	LC50 - 1430mg/l EC50 - 1220mg/l		96 hours 96 hours
Dipropylene glycol monomethyl ether	34590-94-8	Pimephales promelas (fathead minnow)	LC50 - > 10,000 mg/l EC50 - 1,919 mg/l		96 hours 48 hours

Persistence and Biodegradability: Not Available
Bio-accumulative Potential: Not Available
Mobility in Soil: Not Available

SAFETY DATA SHEET

Name: 720 Iso-Free Part A
Page 9 of 12
Date of Issue: 01/08/2025

13. DISPOSAL CONSIDERATION:

Waste generation should be minimized where possible.
Vapours from product residues may create a highly flammable or explosive mixture inside sealed container.
Do not cut, weld or grind used containers unless thoroughly cleaned inside.
Refer to Local/ State Land Waste Management Authority for disposal regulations. Advice flammable nature of product.
Normally suitable for incineration by approved agent if recycling is not feasible.
Liquid waste recycling, refer to Local Waste Authority. Recycle containers if possible or dispose of in authorised landfill.

14. TRANSPORT INFORMATION:



Classified as Dangerous Goods by criteria of the Australian Dangerous Goods Code (ADG Code) for transport by road or rail.

Product Name: 720 Iso-Free Part A
Other Names: Paint
Manufacturer's Product Code: 720 PT A
UN Number: 1263
Packaging Group: III
Dangerous Goods Class & Subsidiary Risk: 3
Hazchem Code: +3YE
Declaration for land shipment: Paint Related Material
Limited Quantity: 5 Litres

Air Transport IATA:

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA), Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

Product Name: 720 Iso-Free Part A
ICAO/IATA Class: 3
Subsidiary risk: None
UN No: 1263
Packaging Group: III
Shipping name: Paint Related Material

Marine Transport:

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

Product Name: 720 Iso-Free Part A
UN No: 1263
Class-primary: 3 Flammable Liquid
Packing Group: III
Shipping Name: Paint Related Material
IMDG Marine Pollutant: Not Determined

Do not load on the same vehicle as:

Class 1:	Explosives
Class 2.1:	Flammable Gases (if both are in bulk)
Class 2.3:	Toxic Gasses
Class 4.2:	Spontaneously Combustible Substances
Class 5.1:	Oxidising Agents
Class 5.2:	Organic Peroxides
Class 7:	Radioactive Substances

SAFETY DATA SHEET

Name: 720 Iso-Free Part A

Page 10 of 12

Date of Issue: 01/08/2025

15. REGULATORY INFORMATION

Poison Schedule: S5**Individual components of 720 Iso-Free Part A on Regulatory Listings:**

(Depending on Colour and Gloss Level).

Naphtha (petroleum), hydro desulfurized heavy: CAS NO: **64742-82-1**: AICS, DSL, TSCA, EINECS, KECI, IVN (CN).Xylene: **CAS No: 1330-20-7**: AICS, DSL, ENCS, TSCA, EINECS, KECI, PICCS, IVN (CN).Butyl Acetate: **CAS No: 123-86-4**: AICS, HSNO.Propylene glycol methyl ether acetate: **CAS No: 108-65-6**: AICS.Ethyl 3-Ethoxypropionate: **CAS No: 763-69-9**: AICS, EINECS.Ethyl Benzene: **CAS No: 100 41-4**: AICS, TSCA, DSL, PICCS, KECL, EINECS, ENCS.2-methylpropan-1-ol: **CAS No: 78-83-1**: AICS, TSCA, DSL, PICCS, KECL, EINECS, ENCSTitanium dioxide: **CAS No: 13463-67-7**: AICS, TSCA, NZIoC, IRAC.Synthetic amorphous Silica: **CAS No: 112929-00-8**: AICS, TSCA, EINECS, DSL/NDL, IRAC.Dipropylene glycol monomethyl ether: **Cas No: 34590-94-8**: AICS, DSL, ENCS, ISHL, KECI, NZIoC, PICCS.Bentonite Clay: **CAS No: 68953-58-2**: AICS, REACH.Carbon Black: **CAS No: 1333-86-4**: AICS, DSL, ENCS, TSCA, EINECS, KECL, PICCS, IRAC.Bismuth Vanadate: **CAS No: 14059-33-7**: AICS, DSL.Phthalocyanine Blue: **CAS No: 147-14-8**: AICS, DSL, ENCS, TSCA, EINECS, NZIoC, PICCS, IECSC, KECI.Monoazo Red: **CAS No: 2786-76-7**: AICS.Isoindolinone Yellow: **CAS No: 36888-99-0**: AICS, DSL.Phthalocyanine Green: **CAS No: 1328-53-6**: AICS.Aluminium Powder: **CAS No: 7429-90-5**: AICS, TSCA, EINECS.Ferric oxide: **CAS No: 1310-14-1**: AICS, TSCA, EINECS.**REGULATORY LISTINGS:**

AICS	Australian Inventory of Chemical Substances
EINECS	European Inventory of Existing Commercial Chemical Substances
TSCA	US Toxic Substances Control Act
DSL	Canadian Domestic Substances List.
IRAC	International Agency for Research on Cancer
PICCS	Philippines Inventory of Chemicals and Chemical Substances
KECL	Korea Existing Chemicals List
ENCS	Japan Existing and New Chemical Substances)
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
DSL/NDL	Canadian Domestic Substances List/Non-Domestic Substance List
NZIoC	New Zealand Inventory of Chemicals
IECSC	Chinese Chemical Inventory of Existing Chemical Substances
KECI	Korea Existing Chemicals Inventory
HSNO	New Zealand Hazardous Substances and New Organisms Act
ISHL	Japan Industrial Safety and Health Law
IVN (CN)	

SAFETY DATA SHEET

Name: 720 Iso-Free Part A

Page 11 of 12

Date of Issue: 01/08/2025

16. OTHER INFORMATION:

IRAC GROUP CLASSIFICATION:

Group 1 Carcinogenic to humans:

Group 2A Probably carcinogenic to humans:

Group 2B Possibly carcinogenic to humans: CAS No: 13463-67-7(dust), 1333-86-4(dust), 100-41-4

Group 3 Not classifiable as to its carcinogenicity to humans: CAS No: 1330-20-7

Group 4 Probably not carcinogenic to humans:

CAS No: CAS Registry Number is a unique numeric identifier that designates only one substance. It has no chemical significance.

TWA: Exposure standard-time weighted average; the average airborne concentration of a particle substance when calculated over a normal eight hour working day, for a five-day week.

STEL: Short-term exposure limit (STEL) is the acceptable exposure limit to a toxic or an irritant substance over a short period of time (time-weighted average), usually 15 minutes. STEL is the maximum concentration of a chemical to which workers may be exposed continuously for a short period of time without any danger to health, safety or work efficiency.

ppm: Parts of vapour or gas per million parts of contaminated air by volume.

mg/m³: Milligrams of substance per cubic metre of air at 25°C and one atmosphere pressure. When entry is in this column only the value is exact; when listed with a ppm value, it is approximate.

LD₅₀: Lethal Dosage represents the individual dose required to kill 50 percent of a population of test animals.

LC₅₀: Lethal Concentrations of the chemical in air that kills 50% of the test animals during the observation period (traditional 4 hours). It can also mean the concentration of a chemical in water.

EC₅₀: The Median Effective Concentration is the statistically derived concentration of a substance in an environmental medium expected to produce a certain effect in 50% of test organisms in each population under a defined set of conditions.

ErC₅₀: Means EC₅₀ in terms of reduction of growth rate after exposure for 72 or 96 hours.

IC₅₀: Half Maximal Inhibitory Concentration is a measure of the effectiveness of a substance in inhibiting a specific biological or biochemical function. This quantitative measure indicates how much of a particular drug or other substance is needed to inhibit a given biological process (or component of a process, i.e., an enzyme, cell, cell receptor or microorganism) by half.

SAFETY DATA SHEET

Name: 720 Iso-Free Part A
Page 12 of 12
Date of Issue: 01/08/2025

16. OTHER INFORMATION:

Toxicity classification: Table 1

Toxicity Classes: Hodge and Sterner Scale					
		Route of Administration			Probable Lethal Dose for Man
		Oral LD ₅₀ (single dose to rats) mg/kg	Inhalation LC ₅₀ (exposure of rats for 4 hours) ppm	Dermal LD ₅₀ (single application to skin of rabbits) mg/kg	
Toxicity Rating	Common Term				
1	Extremely Toxic	1 or less	10 or less	5 or less	1 grain (a taste, a drop)
2	Highly Toxic	1 to 50	10 to 100	5 to 43	4 ml (1 tsp)
3	Moderately Toxic	50 to 500	100 to 1000	44 to 340	30 ml (1 fl. oz.)
4	Slightly Toxic	500 to 5000	1000 to 10000	350 to 2810	600 ml (1 pint)
5	Practically Non Toxic	5000 to 15000	10000 to 100000	2820 to 22590	1 litre (or 1 quart)
6	Relatively Harmless	15000 or more	100000 or more	22600 or more	1 litre (or 1 quart)

Toxicity classification: Table 2

LC/EC/IC ₅₀	< 1 mg/l	very high toxicity
LC/EC/IC ₅₀	1-10 mg/l	high toxicity
LC/EC/IC ₅₀	10-100 mg/l	moderate toxicity
LC/EC/IC ₅₀	>100 mg/l	low toxicity

SDS Effective Date: 01/08/2025

SDS Distribution: The information in this document should be made available to all who may handle the product.

CONTACT POINT

Technical Manager	- Working hours	(02) 9688-1999
	- After hours	0419 260 572

Although this information is presented in good faith and compiled from various sources believed to be accurate, Lacnam Paints make no representations or warranty as to the completeness or accuracy thereof. As the product's performance and suitability depends on various factors, the purchasers of our products should determine for themselves whether the product is suitable for their particular use.

Hazardous according to criteria of Australian Safety Compensation Council